










ARTIC ULTRAFLEX BLUE

Premium Arctic Grade Industrial Wire

Stocked Size	Class K Copper Strand Qty/AWG	Class K Copper Strand Style	Nominal Conductor Outside Diameter	Insulation Thickness	Minimum Finished Outside Diameter	Ampacity** 30°C (86°F)	Ampacity** C (104°F)	Stocked Colors
18 AWG	16/30	Tinned	.047"	.030"	.105"	n/a	n/a	
16 AWG	26/30	Tinned	.059"	.030"	.118"	26	24	
14 AWG	41/30	Tinned	.074"	.030"	.130"	38	36	
12 AWG	65/30	Tinned	.093"	.030"	.150"	44	41	
10 AWG	105/30	Tinned	.118"	.030"	.180"	60	56	
8 AWG	168/30	Bare	.150"	.045"	.240"	85	81	
6 AWG	266/30	Bare	.190"	.060"	.310"	115	106	
4 AWG	420/30	Bare	.240"	.060"	.360"	150	142	
2 AWG	665/30	Bare	.310"	.060"	.430"	205	193	
1 AWG	836/30	Bare	.335"	.080"	.495"	240	223	
1/0 AWG	1064/30	Bare	.390"	.080"	.550"	285	264	
2/0 AWG	1330/30	Bare	.435"	.080"	.600"	325	304	
3/0 AWG	1672/30	Bare	.490"	.080"	.650"	380	355	
4/0 AWG	2109/30	Bare	.530"	.085"	.710"	440	411	
250 MCM	2451/30	Bare	.685"	.095"	.875"	495	461	
350 MCM*	3458/30	Bare	.820"	.095"	1.010"	620	512	
500 MCM	5054/30	Bare	.995"	.110"	1.220"	760	710	