Heat Shrink Tubing Heat Shrink Variety Packages

Dual Wall Heat Shrink Tubing

Dual Wall Adhesive Lined Heat Shrink Tubing with environmental sealing capability is ideal for a variety of applications including automotive and marine wire harness bundles, industrial splices, breakouts, and connector to cable transitions.

-55°C TO 110°C

Features

- · Superior sealing against water and contaminants
- · High 3 to 1 shrink ratio allows for coverage of irregularly shaped connectors and components
- Inner adhesive bonds to plastics, rubber, copper, steel, neoprene, and polyethylene
- VW-1 Flame retardant and flexible
- Shrink temperature: 120°C (248°F)
- Continuous operating temperature: -55°C to 110°C (-67°F to 230°F)

Applications

- · Industrial, electronic, and automotive OEM approvals
- Environmental sealing and strain relief of connectors and terminals
- Sealing and insulation of simple inline splices, repair of damaged wire harnesses
- Abrasion resistance for tubes and pipes



Ordering Guidelines

Our 3:1 ratio shrink covers regular and irregular shapes. For the best balance of recovered wall thickness and adhesive sealant performance, choose a size with an expanded diameter (D) that is about twice the largest diameter of the part to be covered.

shipped folded or cut to 12" lengths

12" Cut Length

Part Number	Diameter	Color
HS-0125-BK-12 HS-0125-CL-12 HS-0125-RD-12	1/8" 1/8" 1/8"	BlackClearRed
HS-0187-BK-12 HS-0187-CL-12 HS-0187-RD-12	3/16" 3/16" 3/16"	BlackClearRed
HS-0250-BK-12 HS-0250-CL-12 HS-0250-RD-12	1/4" 1/4" 1/4"	BlackClearRed
HS-0375-BK-12 HS-0375-CL-12 HS-0375-RD-12	3/8" 3/8" 3/8"	BlackClearRed
HS-0500-BK-12 HS-0500-CL-12 HS-0500-RD-12	1/2" 1/2" 1/2"	BlackClearRed
HS-0750-BK-12 HS-0750-CL-12 HS-0750-RD-12	3/4" 3/4" 3/4"	BlackClearRed
HS-1000-BK-12 HS-1000-CL-12 HS-1000-RD-12	1" 1" 1"	BlackClearRed

48" Cut Length

Diameter

1/8"

Color

Black

Clear Red

Black Blue

Clear

Green Red

O White

Yellow

Black

Blue Clear

Green

Red

White

Yellow

Black

Blue

Clear

Green Red

White

Yellow

Black Blue

Clear Green Red

White Yellow Black

Blue Clear

Green

Red

O White

Yellow

Black

Blue Clear

Green Red White Yellow Black Red Black Blue Clear

Green

Red

White

Yellow

1 1/2"

1 1/2"

Brown* Orange*

Part Number

Part Number	
HS-0125-BK-48 HS-0125-CL-48 HS-0125-RD-48	
HS-0187-BK-48 HS-0187-BL-48 HS-0187-CL-48 HS-0187-GR-48 HS-0187-RD-48 HS-0187-WT-48 HS-0187-YL-48	
HS-0250-BK-48 HS-0250-BN-48 HS-0250-OR-48 HS-0250-GL-48 HS-0250-GR-48 HS-0250-GR-48 HS-0250-WT-48 HS-0250-WT-48	
HS-0375-BK-48 HS-0375-BL-48 HS-0375-CL-48 HS-0375-GR-48 HS-0375-RD-48 HS-0375-WT-48 HS-0375-YL-48	
HS-0500-BK-48 HS-0500-BL-48 HS-0500-CL-48 HS-0500-GR-48 HS-0500-RD-48 HS-0500-WT-48 HS-0500-YL-48	
HS-0750-BK-48 HS-0750-BL-48 HS-0750-CL-48 HS-0750-GR-48 HS-0750-RD-48 HS-0750-WT-48 HS-0750-YL-48	
HS-1000-BK-48 HS-1000-BL-48 HS-1000-CL-48 HS-1000-GR-48 HS-1000-RD-48 HS-1000-WT-48 HS-1000-YL-48	
HS-1250-BK-48 HS-1250-RD-48	
HS-1500-BK-48 HS-1500-BL-48 HS-1500-CL-48 HS-1500-GR-48	

125-CL-48 125-RD-48	1/8" 1/8"
187-BK-48 187-BL-48 187-CL-48 187-GR-48 187-RD-48 187-WT-48 187-YL-48	3/16" 3/16" 3/16" 3/16" 3/16" 3/16"
250-BK-48 250-BN-48 250-OR-48 250-BL-48 250-CL-48 250-GR-48 250-GR-48 250-RD-48 250-WT-48 250-YL-48	1/4" 1/4" 1/4" 1/4" 1/4" 1/4" 1/4" 1/4"
375-BK-48 375-BL-48 375-CL-48 375-GR-48 375-RD-48 375-WT-48 375-YL-48	3/8" 3/8" 3/8" 3/8" 3/8" 3/8"
500-BK-48 500-BL-48 500-CL-48 500-GR-48 500-RD-48 500-WT-48 500-YL-48	1/2" 1/2" 1/2" 1/2" 1/2" 1/2" 1/2"
750-BK-48 750-BL-48 750-CL-48 750-GR-48 750-RD-48 750-WT-48 750-YL-48	3/4" 3/4" 3/4" 3/4" 3/4" 3/4"
000-BK-48 000-BL-48 000-CL-48 000-GR-48 000-RD-48 000-WT-48 000-YL-48	1" 1" 1" 1" 1" 1"
250-BK-48 250-RD-48	1 1/4" 1 1/4"
500-BK-48 500-BL-48 500-CL-48 500-GR-48	1 1/2" 1 1/2" 1 1/2" 1 1/2"

*To significantly reduce shipping cost, 48" heat shrink is

Dual Wall Adhesive Lined Crosslinked Polyolefin*

		AS SUPPLIED				AFTER RECOVERY							
Part Number	Size	er Size	Minimur Diame		Nom Wall Thi		Maximur Diame		Total Non Thickne		Nom Adhesi		Standard Lengths
		in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	
HS-0125	1/8"	0.126	3.2	0.016	0.40	0.039	1.0	0.033	0.85	0.014	0.35	12, 48	
HS-0187	1/16"	0.185	4.7	0.016	0.40	0.059	1.5	0.041	1.05	0.018	0.45	12, 48	
HS-0250	1/4"	0.252	6.4	0.018	0.45	0.079	2.0	0.043	1.10	0.018	0.45	12, 48	
HS-0375	3/8"	0.370	9.4	0.024	0.60	0.118	3.0	0.057	1.45	0.018	0.45	12, 48	
HS-0500	1/2"	0.500	12.7	0.024	0.60	0.157	4.0	0.059	1.50	0.018	0.45	12, 48	
HS-0750	3/4"	0.748	19.0	0.030	0.75	0.236	6.0	0.079	2.00	0.026	0.65	12, 48	
HS-1000	1"	0.992	25.2	0.030	0.75	0.331	8.4	0.079	2.00	0.026	0.65	12, 48	
HS-1250	1 1/4"	1.181	30.0	0.031	0.80	0.394	10.0	0.087	2.20	0.030	0.75	48	
HS1500	1 1/2"	1.570	39.9	0.033	0.85	0.593	13.7	0.098	2.50	0.039	1.00	48	

HS-1500-RD-48

HS-1500-WT-48

HS-1500-YL-48

*Special Order

Heat Shrink Service Kits available — see page 70



Dual Wall Heat Shrink Packs

3 to 1 Ratio Adhesive Lined Heat Shrink packaged in a variety of sizes of red or black, or by size in a mix of colors.





Size Variety Packs

- 10 pieces in 12" lengths
- 2 each of 1/8", 1/4", 3/8", 1/2", 3/4"

Color Mix Packs

- 10 pieces in 12" lengths
- 1 each of yellow, green, blue, white
- · 2 each black, red, clear

Dual Wall Size Variety Packs

Part Number	Diameter Mix	Color
HS-BLACK-PKG	1/8" to 3/4"	Black
HS-RED-PKG	1/8" to 3/4"	Red

Dual Wall Color Mix Packs

Part Number	Diameter
HS-250-PKG	1/4"
HS-375-PKG	3/8"
HS-500-PKG	1/2"
HS-750-PKG	3/4"

O White Red Green Clear Blue

Yellow

Color Mix Black





Heavy Wall Shrink Packs



Size Variety Packs

- 10 pieces in 12" lengths
- 3 each of 1/3", 1/2", and 3/4"
- 1 of 1"

2-Color Black/Red Packs

- 4 pieces in 12" lengths
- 2 each of red and black



-55°C TO 110°C

Heavy Wall Size Variety Packs

Part Number	Diameter Mix	Color
HSHD-BLACK-PKG	1/3" to 1"	Black
HSHD-RED-PKG	1/3" to 1"	Red

Heavy Wall Black/Red Packs

Part Number	Diameter	Color Mix
HSHD-350-PKG	1/3"	Black
HSHD-500-PKG	1/2"	Red
HSHD-750-PKG	3/4"	
HSHD-1100-PKG	1"	

Automatic Ignition Torch

The heavy duty **Pro-Torch™ Butane Torch** provides a strong and stable flame for demanding jobs where the highest BTU output is required. Precision orifice and controls. Ergonomic grip for comfort at most any angle.

- State of the art waterproof Piezo Electronic Ignition
- Large fuel tank provides up to 200 minutes use per filling
- Powerful high-output wind-resistant adjustable flame
- Heavy duty ribbed aluminum body with comfort grip
- · Easily refilled with any brand of butane

Length 4.73" Height 6.9" Weight 10.6 oz.

Part Number PTB-500



Custom Heat Shrink Variety Packs

Need specific types, colors, or sizes? We configure custom variety packs with the shrinks you use most. Give us a call!